

PPW-C24 Automatic Pallet Washer


Cherry's Industrial Pallet Washer minimizes the risk of introducing Salmonella, E-coli, Listeria, Allergens, dust, dirt and other contaminants into the WIP and production areas.

- Automatically clean, rinse, sanitize, and dry plastic pallets and freezer spacers.
- High impact nozzles remove blood, fats, powders, dyes, oils, grease, and loose debris that can accumulate on pallets.
- Upgradable modular design consisting of independent, interlinking sections - Spray Wash, Fresh Water Rinse, and Dry.
- Budget friendly start with base module and add other modules at a later time.
- All Stainless Steel Construction with painted finish
- No overspray and cross-contamination of water
- Made in the USA



Automatically cleans, rinses, and dries up to 100 pallets an hour.

Multi-Stage Design



Stage 1 Washer: Spray Only Model #: PPW-C24-SZ3

Base model includes spray module with heated water. Detergent can be added with this module.



Stage 2 Washer: Spray and Rinse Model #: PPW-C24-SZ5-FRZ1

Includes both the spray and fresh water rinse modules. Buffer zones within the modules prevent cross-contamination of water.



Stage 3 Washer: Spray, Rinse, and Dry Model #: PPW-C24-SZ5-FRZ1-DAHZ5

Includes the spray module, fresh water rinse module, and any of our available selection of dry off modules.

Attributes & Specifications



PALLET WASHER MODEL	SZ-3	SZ-5
SPRAY ZONE	36"	60"
LxWxH	108" x 8" x 50"	132" x 8" x 50"
TANK	275 Gal	400 Gal
PUMP OUTPUT	100 GPM at 50 PSI	150 GPM at 50 PSI
ELECTRIC MOTOR	5 HP	7.5 HP
PANEL	NEMA 12	NEMA 12
POWER	480V/3 PH/60Hz	480V/3 PH/60Hz
TYPE OF CONTROLS	Start/Stop Push Button	Start/Stop Push Button

RINSE MODEL	FRZ1
SPRAY ZONE	12"
LxWxH	48" x 8" x 50"
TANK	NA
PUMP OUTPUT	3 GPM
PANEL	NEMA 12
WATER SOURCE	Hot/Cold by Customer
TYPE OF CONTROLS	Start/Stop Push Button
SANITIZER	Optional w/DST-11

DRYER MODEL	DAZ5	DAHZ5
DRY ZONE	60"	60"
BUFFERS	18" Inlet/Outlet	18" Inlet/Outlet
LxWxH	96" x 8" x 50"	96" x 8" x 50"
BLOWER	20 HP	20 HP
VERTICAL AIR KNIVES	(8) with (4) on each side	(8) with (4) on each side
AIR TEMP	Non-Heated	up to 200° F
INSULATED WALLS	Yes	Yes

BLOWER MODEL	SB0Z1.5
DRY ZONE	18"
BUFFERS	18" Inlet/12" Outlet
LxWxH	48" x 8" x 50"
BLOWER	10 HP
VERTICAL AIR KNIVES	(4) with (2) on each side
AIR TEMP	Non-Heated
INSULATED WALLS	No

OPTIONS



INSULATION - Increases R value which also helps maintain water temperatire. (R value of 4) Noise Reducer; Covered in stainless steel cladding.



ELECTRONIC EYE - Belt stops when eye sensor is tripped.



DOOR SAFETY SWITCH -Automatically shuts down machine when door opens.



BEACON LIGHTS - Mounted on the top of the panel. Choose from either 1 color or 3 colors.



MICRON BAG FILTER - Filters 100% of the solution prior to going to the spray headers.



ALLEN BRADLEY PLC & 600
Panel View touch-interface control panel.

DISTRIBUTED BY:



DST-11 Chemical Siphon Valve Injects the sanitizing agent into the rinse water module.



MARINE CLEAN-OUT DOOR Provides front access to a tank.
16" in diameter.



600 Morse Ave. Elk Grove Village, IL 60007

www.Cherrysind.com 800-350-0011

